

|                       |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT</b>        | <b>15050</b>                                                                                                                                                                                                                                                                                                                                 |
| <b>USE</b>            | Ceramics, metals, plastics.                                                                                                                                                                                                                                                                                                                  |
| <b>PROPERTIES</b>     | Medium viscosity adhesive which provides strong and elastic bonding to many materials including ceramics, metals and plastics (except PE, PP and PTFE).                                                                                                                                                                                      |
| <b>DESCRIPTION</b>    | <p><b>Basis:</b> EVA &amp; synthetic resins</p> <p><b>Composition:</b> Non-hazardous according to Directive 1999/45/CE</p> <p><b>Color:</b> Yellow</p> <p><b>Diameter:</b> Ø 14,4 ± 0,40 mm</p> <p><b>Long:</b> 300 mm ± 5 mm</p>                                                                                                            |
| <b>TECHNICAL DATA</b> | <p><b>Viscosity (180 °C):</b> 9.000 ± 2.500 CP</p> <p><b>Softening time:</b> 88 ± 5 °C</p> <p><b>Aplication temp:</b> 180 °C - 210 °C</p> <p><b>Open time:</b> 30" - 40" (medium)</p> <p><b>Bond time:</b> 15" - 20"</p>                                                                                                                     |
| <b>PACKAGING</b>      | <p>Box 10 kg</p> <p>Pallet 600 kg</p>                                                                                                                                                                                                                                                                                                        |
| <b>INFORMATION</b>    | All components of this product comply with the requirements of Regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food, and are approved for use in adhesives for indirect food contact by the Food & Drug Administration (Code of Federal Regulations, Title 21, Section 175.105 "Adhesives"). |

REVIEW 5 / 5 / 2014

## COMERSIM S.A.U.

Pol. Ind. "Ampliación Comarca 1", Calle L 15 - 17  
31160 ORKOIEN - Navarra - Spain

T +34 948 33 04 12  
F +34 948 33 02 53

simes@grupodesa.es  
www.simes.es

## EXPORT

export@grupodesa.es  
www.simes.es/hotmelt/en

T +34 948 33 52 66  
F +34 948 33 02 53



Management  
System  
ISO 9001:2008

www.tuv.com  
ID 1100008007

